



MOMENTA RX5

MINERAL

PRODUCT DESCRIPTION:

Momenta RX5 is a high-performance heavy-duty engine oil based on high quality mineral base stocks and advanced additives technology providing superior dispersancy/detergency, wear and oxidation resistance properties. Ideal for mixed fleet use having a variety of different makes of heavy-duty diesel engines and using fuels of a wide range.

APPLICATION:

Recommended for modern heavy-duty engines, wide range of turbo-charged or naturally aspirated diesel engines, generators, trucks, construction cars, passenger cars or mixed car group comprising diesel and gasoline cars. It is recommended for automotive diesel engine of passenger cars and light commercial vehicles where the OEM recommends API CF-4 or earlier specification.

FEATURES & BENEFITS:

- Fuel saving and reduces maintenance expenses for machines and engines.
- Very long oil changing period.
- Resists oil thickening and the formation of carbon, varnish and sludge deposits.
- Good viscosity control.
- Prolonged engine life.
- Safeguards the moving parts.
- Keeps engine Clean.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CF-4/SJ
- MB 228.2
- ACEA E2-96, A3/B3
- MTU Type-2
- MAN 3275-1
- VOLVO VDS
- MACK EO/K2
- CES 20075/74/73

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA RX5						
Grade			15W-40	15W-50	20W-50	20W-60	25W-60	40	50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	15.3	15.2	19.8	24.2	24.0	15.5	20.2
Viscosity Index (min)	D2270	-	135	135	120	120	115	95	95
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-33	-33	-24	-24	-21	-9	-9
TBN	D2896	mg KOH/g	9	9	9	9	9	9	9
CCS	D5293	m.Pa.S	<7000 (-20°C)	<7000 (-20°C)	<9500 (-15°C)	<9500 (-15°C)		-	-

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.