



OPTIMUS FIRE RESISTANT HYDRAULIC FLUID HFC

PRODUCT DESCRIPTION:

Optimus fire resistant hydraulic fluid HFC is water glycol hydraulic fluid technology with improved fire resistance while protecting equipment under severe service conditions. It is designed particularly for hydraulic systems utilizing vane, gear and piston hydraulic pumps used in, for example, the steel, aluminum and die-casting industries. It is very shear stable offering enhanced corrosion resistance performance and seal compatibility, providing excellent pump lubrication which can help to extend equipment service life.

APPLICATION:

- Hydraulic systems utilizing vane, gear and piston hydraulic pumps
- Hydraulic and oil circulation systems operating in conditions subject to fire hazards

FEATURES & BENEFITS:

- Inherent resistance to fire hazards
- Excellent anti-wear properties helping to extend component life
- Long fluid life due to high oxidation resistance

PERFORMANCE LEVELS: Meets and Exceeds:

- ISO L-HFC (ISO/DIS 12922)
- FM Global Standard 6930

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	OPTIMUS TORQUE WG
ISO VG			46
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	46
Viscosity Index	ASTM D-2270	-	195
Pour Point (max)	ASTM D-97	°C	-48
Copper Corrosion, 24Hrs, 50°C	ISO 2160	-	1B
Color	Visual	-	Red

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.