



## OPTIMUS SHOCK ABSORBER OIL

### PRODUCT DESCRIPTION:

Optimus Shock Absorber Oil is formulated using high-performance synthetic base oils & combination of additives to provide excellent damping effect for shock absorbers used in motorcycles. This oil has excellent viscosity temperature behavior, oxidation stability & anti-foam properties. It has also a very good seal compatibility.

### APPLICATION:

Recommended as hydraulic fluid for front fork motorcycles & other shock absorbers mechanism.

### FEATURES & BENEFITS:

- Increase the life of shock absorber
- Excellent seal compatibility
- Longer oil life
- Excellent damping effect
- Excellent low temperature properties

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	Optimus Shock Absorber Oil
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	32
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	5.9
Viscosity Index	ASTM D-2270		130
Flash Point (min)	ASTM D-92	°C	210
Pour Point	ASTM D-97	°C	-24

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.