



## RACE 2T

### 2 STROKE ENGINE OIL

#### PRODUCT DESCRIPTION:

Race 2T is a lubricant which is designed to provide excellent performance in two-stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead free fuels. This is a high technology product combining a perfect balance of highly refined base stocks and the latest additives technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.

#### APPLICATION:

Race 2T oil is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

#### FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

#### PERFORMANCE LEVEL: Meets or Exceeds:

- API TC
- JASO FD
- ISO EGD

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	RACE 2T
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	9
Viscosity Index	ASTM D2270	-	120
Density@15°C/ 60°F	ASTM D4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-24
Color	Visual	-	Blue

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.