



RACE 4T NANO

SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

Race 4T Nano is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. Race 4T Nano is excellent in maintaining high engine power and fuel economy with longer drain interval.

APPLICATION:

Recommended for all motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets and Exceeds:

- API SJ
- JASO MA

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | RACE 4T NANO | | | | | |
|------------------------------------|-------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|
| | | | 5W-40 | 10W-30 | 10W-40 | 10W-60 | 20W-40 | 20W-50 |
| Grade | | | 5W-40 | 10W-30 | 10W-40 | 10W-60 | 20W-40 | 20W-50 |
| Kinematic Viscosity @ 104°F /40°C | ASTM D-7042 | cSt | 94.25 | 76.45 | 99.5 | 181.7 | 122.7 | 179.5 |
| Kinematic Viscosity @ 212°F /100°C | ASTM D-7042 | cSt | 14.8 | 11.9 | 14.7 | 24.9 | 14.9 | 19.8 |
| Viscosity Index | ASTM D-2270 | - | 165 | 151 | 155 | 170 | 125 | 128 |
| SP. Gravity @15°C/ 60°F | ASTM D-4052 | g/cm ³ | 0.856 | 0.867 | 0.866 | 0.861 | 0.890 | 0.891 |
| Flash Point (min) | ASTM D-92 | °C | 228 | 228 | 226 | 226 | 238 | 236 |
| Pour Point (max) | ASTM D-97 | °C | -42 | -39 | -39 | -36 | -24 | -24 |
| TBN | ASTM D-2896 | Mg KOH/g | 6 | 6 | 6 | 6 | 6 | 6 |
| CCS, (°C) | ASTM D-5293 | m.Pa.S | <6600 (-30) | <7000 (-25) | <7000 (-25) | <7000 (-25) | <9500 (-15) | <9500 (-15) |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

[™]Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.