



## SHIFT EXTRA EXTREME PRESSURE AUTOMOTIVE GEAR OIL

### PRODUCT DESCRIPTION:

Shift Extra are high quality gear and transmission lubricants blended from solvent-refined mineral base oils and selected Sulphur and phosphorous chemical additives. Due to their high shear stability they provide excellent protection for gears and can be used over a wide range of temperature.

### APPLICATION:

Shift Extra is recommended for automotive transmission and gear where API GL-4 performance is required. It's also suitable for other automotive type equipment, operated under high speed, low torque and low-speed/high torque conditions.

### FEATURES & BENEFITS:

- Excellent lubrication without channeling at low-temperatures.
- Superior protection against rusting, pitting and corrosion.
- Suitable for heavy duty service in truck and bus gears operating at high temperatures.
- Provides good protection against wear.
- Formulated for automotive high speed gears.

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	90	140	80W-90	85W-90	80W-140	85W-140	75W-90
API	GL-4	GL-4	GL-4	GL-4	GL-4	GL-4	GL-4
MIL	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B	MIL-L-2105B

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SHIFT EXTRA						
			90	140	80W-90	85W-90	80W-140	85W-140	75W-90
KV@ 104°F /40°C	D7042	cSt	200.0	405.1	142.0	200	225	405.0	86.1
KV @ 212°F /100°C	D7042	cSt	17.5	28.3	15.6	17.5	28.5	28.2	14.4
Viscosity Index	D2270	-	96	97	114	96	165	96	174
SP. Gravity @15°C	D4052	g/cm3	0.899	0.902	0.895	0.899	0.880	0.905	0.845
Flash Point (min)	D92	°C	230	236	220	230	218	234	214
Pour Point (max)	D97	°C	-9	-9	-27	-15	-27	-12	-42
Brookfield Viscosity	D2983	cp	-	-	<150,000 (-26C)	<150,000 (-12C)	<150,000 (-12C)	<150,000 (-26C)	<150,000 (-40C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.