



SHIFT EXTRA 2330 MANUAL TRANSMISSION OIL

PRODUCT DESCRIPTION:

Shift Extra 2330 is a high-quality transmission oil, suitable for nearly all manual gear boxes of passenger cars. It is specially recommended for PSA manual gear boxes with extended drain interval and friction modifier additive adapted to PSA manual gear boxes.

APPLICATION:

Shift Extra is tested under strict conditions, this oil meets the general performance requirements of most brands and models in all weather conditions.

FEATURES & BENEFITS:

- Smooth gear shifting.
- Significantly extended transmission life
- High resistance to oil degradation
- Provides good protection against wear and corrosion
- Reduced cost of maintenance due to long drain intervals

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	75W-80
API	GL-4
PSA	B71 2330
PSA	9730 A8
MB	235.10
FORD	WSDM2C200-D
FORD	ESDM2C186-A
GM	1940182
GM	1940768
HONDA	MTF 94
VOLVO	97308/97309/97310
NISSAN	MT-XZ

* Phosphorus limit exceeds.

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SHIFT EXTRA 2330
			75W-80
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	9.1
Viscosity Index	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42
Brookfield Viscosity	D2983	cp	142,000(-40C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.