



STOP DOT 4 LV

PRODUCT DESCRIPTION:

Stop Dot 4 LV is a very high specification Brake and Clutch Fluid which conforms to the latest ISO 4925 Class 6 standard. Its exception low temperature viscosity allows an easier fluid circulation in micro-valves of anti-locking systems for better response of ABS, ESP and ASR high pressure systems. The high wet boiling point of Stop DOT 4 LV as compared to conventional DOT 4 enables longer product lifetime.

APPLICATION:

Stop Dot 4 LV brake fluid can be used in all vehicles where ISO 4925 Class 6 specification is required. It is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ABS (Anti-lock Braking System), ESP (Electronic Stability Program) and ASR (Acceleration Slip Regulation). Stop DOT 4 LV is mixable with DOT 3, DOT 4 and DOT 5.1 NON-SILICONE BASE products. Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

FEATURES & BENEFITS

- Optimal ABS properties.
- Exception chemical stability.
- High lubricating power.
- Exceptional low viscosity at low temperature.
- Higher Dry and Wet boiling points.
- Miscibility with all brake fluids of the same specification.

TYPICAL PROPERTIES:

P ARAMETERS	STOP DOT 4 LV
ISO	4925 Class 6
FMVSS 116	DOT 4
SAE	J 1704
MB	331.0
VW	501.14 (TL 766-Z)
FORD	WSS-M6C65-A2/M6C57-A2
BMW	QV 34001

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with brake fluid may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used brake fluid in to drains or the environment. Dispose to an authorized collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.