



## TORQUE HVLP

### PRODUCT DESCRIPTION:

Torque HVLP hydraulic oil is a high viscosity index antiwear hydraulic oil. It is formulated to have a high viscosity index and a low pour point for use over a wider temperature range than conventional antiwear hydraulic oils. It provides excellent wear protection for hydraulic pumps and motors, has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life, and protects hydraulic system components against rust and corrosion.

### APPLICATION:

For mobile and static hydraulic applications of industrial and other equipment. Hydraulic cranes and lifts, loaders, reach trucks, forklifts, excavators, dumpers, loading ramps, and tailboards. Sometimes recommended for: hydraulic systems of metalworking machines, or circulation systems of industrial machinery.

### FEATURES & BENEFITS:

- Excellent demulsibility
- Very good corrosion protection to steel
- Good corrosion protection to copper
- High ageing stability / high oxidation stability
- Good AW wear protection
- Very good hydrolytic stability
- Excellent filtration behavior (dry, wet)
- Low foaming
- Excellent air release

### PERFORMANCE LEVELS: Meets or Exceeds:

- DIN 51524 Part 3, Type HVLP

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	TORQUE HVLP					
			15	22	32	46	68	100
Grade			15	22	32	46	68	100
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	15	22	32	46	68	100
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	3.74	4.77	6.0	7.9	10.6	14
Viscosity Index	ASTM D2270	-	140	140	146	143	144	142
Density@15°C/ 60°F	ASTM D4052	g/cm <sup>3</sup>	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	180	204	200	200	200	200
Pour Point (max)	ASTM D97	°C	-33	-33	-35	-35	-35	-35

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.