



VECTOR EP

PRODUCT DESCRIPTION:

Vector EP gear lubricants are high-performance, multipurpose mineral oil based lubricants designed for many types of industrial gear lubrication services where loads and shock loadings are high.

APPLICATION:

Vector EP gear oils are recommended for industrial enclosed gearing where an AGMA extreme pressure lubricant is specified. It is designed for use in industrial gear boxes including in crushers, hoists, conveyors, winches, machine tools and lathes. It can also be used in chain drives, sprockets, plain and anti-friction bearings and slide guides.

FEATURES & BENEFITS:

- High thermal stability EP system helps maintain clean gear and bearing surfaces
- Effective EP system forms a protective film in areas of metal-to-metal contact, minimizing wear rates and maintaining efficient transfer of power
- Effective oxidation inhibitors and copper passivator minimize oil oxidation, limiting viscosity increase and promoting long drain intervals

PERFORMANCE LEVELS: Meets or Exceeds:

- AGMA EP 9005-E02
- DIN 51517-3 (CLP)
- MAG Cincinnati, Cincinnati Machine P-63 (ISO 68), P-76 (ISO 100), P-77 (ISO 150), P-74 (ISO 220), P-59 (ISO 320), P-35
- (ISO 460), P-78 (ISO 100)
- U.S. Steel 224 Specification (ISO 220, 320, 460, 680)
- FLENDER

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VECTOR EP							
			68	100	150	220	320	460	680	1000
ISO VG			68	100	150	220	320	460	680	1000
AGMA Grade			2 EP	3 EP	4 EP	5 EP	6 EP	7 EP	8 EP	8 EP
API Gravity	-	-	31	30	29	28	27	26	26	25
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	68.1	107.0	153.4	216.9	319.1	452.2	665.6	1000
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Viscosity Index (min)	ASTM D2270	-	95	95	95	95	95	95	95	95
Flash Point (min)	ASTM D92	°C	200	200	200	200	200	200	200	200
Pour Point (max)	ASTM D97	°C	-9	-9	-9	-9	-9	-9	-9	-9
Timken OK Load	-	lb	65	65	65	65	65	65	65	65
FZG Pass Stage	ASTM D5182	-	12	12	12	12	12	12	>12	>12

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.