



## VELOCITY GX7 SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity GX7 is semi synthetic engine oil a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

### APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Excellent protection against sludge and varnish deposits

### PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SJ/CF

### TYPICAL PROPERTIES:

| PARAMETERS                         | TEST METHOD | UNIT              | VELOCITY GX7 |              |
|------------------------------------|-------------|-------------------|--------------|--------------|
|                                    |             |                   | 10W-30       | 10W-40       |
| Grade                              |             |                   | 10W-30       | 10W-40       |
| Kinematic Viscosity @ 104°F /40°C  | ASTM D7042  | cSt               | TBR          | TBR          |
| Kinematic Viscosity @ 212°F /100°C | ASTM D7042  | cSt               | 11.6         | 15           |
| Viscosity Index (min)              | ASTM D2270  | -                 | 145          | 145          |
| Density@15°C/ 60°F                 | ASTM D4052  | g/cm <sup>3</sup> | TBR          | TBR          |
| Flash Point (min)                  | ASTM D92    | °C                | 220          | 220          |
| Pour Point (max)                   | ASTM D97    | °C                | -39          | -39          |
| TBN                                | ASTM D2896  | mg KOH/g          | 6            | 6            |
| CCS                                | ASTM D5293  | m.Pa.S            | <6600(-30°C) | <6600(-30°C) |

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

### ™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.