



VELOCITY NANO PRO

PRODUCT DESCRIPTION:

Velocity Nano Pro oils are formulated from premium quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high performance gasoline engine cars equipped with direct-injection, multi valve & turbo charger technologies.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API Service Category SN.

FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions
- Special cleaning additive to help prevent the formation of sludge and harmful deposits
- Optimal engine operating temperature, owing to thermal control formula
- Limits formation of deposits on the most loaded engine parts
- Provides safe operation of catalytic exhaust converters
- Resistant to extreme thermal load, due to high quality of base oil
- Enables fast and easy start in extreme temperature conditions
- Extra cleaning performance

API LICENSE:

- SAE 0W-20 • SAE 5W-20 • SAE 5W-30 • SAE 5W-40 • SAE 10W-30 • SAE 10W-40 • SAE 20W-50



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-16	0W-20	5W-20	5W-30	10W-30	5W-40	10W-40	15W-40	20W-50
API	SN (RC)	SN (RC)	SN (RC)	SN (RC)	SN (RC)	SN	SN	SN	SN
ILSAC	-	GF-5	GF-5	GF-5	GF-5	-	-	-	-
GM	-	DEXOS1	DEXOS1	DEXOS1	-	-	-	-	-
CHRYSLER	-	MS6094M	MS6094M	MS6094M	MS6094M	-	-	-	-
FORD	-	947A	945A	946A	-	-	-	-	-

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY NANO PRO							
			0W-20	5W-20	5W-30	5W-40	10W-30	10W-40	15W-40	20W-50
KV@104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
KV@212°F /100°C	D7042	cSt	8.3	8.4	10.3	14.8	10.2	15	14.9	19.9
Viscosity Index (min)	D2270	-	150	150	160	160	145	145	135	120
SP. Gravity @15°C	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-39	-36	-33	-24
TBN	D2896	mgKOH/g	7	7	7	7	7	7	7	7
CCS	D5293	m.Pa.S	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	<7000 (-20°C)	<9500 (-15°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.