



VELOCITY SPECIFIC RN17 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Velocity Specific RN17 is a high-performance engine oil developed to meet RN17, the latest specification for Renault vehicles (Renault, Dacia, Samsung) fitted with TGDI and EURO VI engines. The 100% Synthetic base stock provides a high thermal stability and low volatility which ensures an exceptional resistance to varnish and sludge formation and maintains engine cleanliness. Outstanding oxidation resistance of the lubricant results in extended oil drain intervals set by the car manufacturer. Velocity Specific RN17 meets high quality standards, facilitating optimum engine performance and extended component life by virtue of fast and effective lubrication across a wide temperature range.

APPLICATION:

Velocity Specific RN17 is designed for most gasoline engines (except Renault Sport & Alpine) and new Euro 6d diesel engines (2018 onwards) as well as all Diesel without DPF.

Velocity Specific RN 17 is suitable for use in vehicles where a Renault RN 17 specification SAE 5W30 lubricant is required. The RN17 standard does not apply to diesel engines requiring RN0720.

FEATURES & BENEFITS:

- Advanced engine protection under all driving conditions.
- Prolongs the life and maintain the efficiency of particulate filters and catalytic converters.
- Keep engine clean from deposits for optimal efficiency and long life.
- Excellent protection against viscosity and thermal breakdown

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADE	5W-30
ACEA-22	C3
RENAULT	RN17
MB	226.52

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY SPECIFIC RN17
SAE Grades			5W-30
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	11.9
Viscosity Index (min)	D2270	-	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-39
TBN	D2896	mg KOH/g	8.5
CCS	D5293	m.Pa.S	<6600 (-30°C)

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.