



## VELOCITY NANO PLUS PAO FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity Nano Plus PAO is a premium quality lubricant formulated with PAO (Polyalphaolefin) base stocks which helps deliver outstanding engine protection in recent cars fitted with Gasoline and Diesel engines, naturally aspirated or turbo-charged, indirect or direct injection. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

### APPLICATION:

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

### FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40
API	SL/CF	SN/CF
ACEA	A3/B4	A3/B4
VOLVO	95200356	-
Porsche	-	A40
MB	226.5	226.5
	229.3	229.3
	229.5	229.5
RENAULT	RN0700	RN0700
	RN0710	RN0710
VW	502 00	502 00
	505 00	505 00
BMW	LL-01	LL-01
PSA	-	-
Ford	-	WSS-M2C-937-A

### TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	VELOCITY NANO PLUS PAO	
			0W-30	0W-40
Grade				
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	65.1	80.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.80	14.5
Viscosity Index	D-2270	-	180	190
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.844	0.845
Flash Point (min)	D-92	°C	230	230
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	10	10
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.