



VELOCITY NANO PLUS SYNTHETIC

PRODUCT DESCRIPTION:

Velocity Nano Plus is an advanced fully synthetic engine oil designed to help deliver outstanding engine protection in recent cars fitted with Gasoline and Diesel engines, naturally aspirated or turbo-charged, indirect or direct injection. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

APPLICATION:

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control

OEM Approvals:

- MB-Approval 229.5 (SAE 5W-30)
- MB-Approval 229.5 (SAE 5W-40)
- VW Standard 502 00 /505 00 (SAE 5W-40)
- VW Standard 502 00 /505 00 (SAE 5W-30)
- Porsche Oil Category A40 (SAE 5W-40)

API LICENSE:

- SAE 0W-20
- SAE 0W-40
- SAE 5W-20
- SAE 5W-30
- SAE 5W-40



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-20	0W-30	0W-40	5W-20	5W-30	5W-40
API	SN	SL/CF	SN/CF	SN	SN/SL/CF	SN/CF
ACEA-23	A5/B5	A3/B4	A3/B4	A5/B5	A3/B4	A3/B4
VOLVO	-	95200356	-	-	-	-
Porsche	-	-	A40	-	-	A40
MB	-	226.5 229.3 229.5	226.5 229.3 229.5	-	226.5 229.3 229.5	226.5 229.3 229.5
RENAULT	-	RN0700 RN0710	RN0700 RN0710	-	RN0700 RN0710	RN0700 RN0710
VW	-	502 00 505 00	502 00 505 00	-	502 00 505 00	502 00 505 00
BMW	-	LL-01	LL-01		LL-01	LL-01
PSA	-	-	-	-	-	B71 2296
Ford	-	-	WSS-M2C-937-A	WSS-M2C-925-B	-	-
LANDROVER	-	-		STJLR.03.5004	-	-


TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	VELOCITY NANO PLUS					
			0W-20	0W-30	0W-40	5W-20	5W-30	5W-40
Grade			TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	8.9	11.8	14.9	8.8	11.6	15
Viscosity Index (min)	D2270	-	150	160	170	150	160	160
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-39	-39

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.