



## VELOCITY NANO MINERAL

### PRODUCT DESCRIPTION:

Velocity Nano oil is formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. This oil is designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low temperature performance over the life of the oil.

### APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines and portable power equipment.

### FEATURES & BENEFITS:

- "Viscous" formula well-suited to long stays in hot countries (20W for example)
- Particularly recommended for urban driving
- Resistant to extreme thermal load due to high quality of base oil
- Protects engines against deposits
- Standard drain interval

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SM/CF
- ACEA A3/B3
- VW 501.01 / 505.00
- RN 700, RN 710

### API LICENSE:

- SAE 20W-50
- SAE 15W-40



### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY NANO	
			15W40	20W50
Grade			15W40	20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	15	20
Viscosity Index (min)	ASTM D2270	-	135	120
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm3	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-33	-24
TBN	ASTM D2896	mg KOH/g	8	8
CCS	ASTM D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.