



## VELOCITY NANO PLUS MINERAL

### PRODUCT DESCRIPTION:

Velocity Nano Plus mineral oils are formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high performance gasoline engine cars equipped with direct-injection, multi valve & turbo-charger technologies.

### APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SN.

### SUITABLE FOR:



### FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

### API LICENSE:

- SAE 20W50



### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

This product is recommended for use in applications requiring:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.1
- VW 505 00


**TYPICAL PERFORMANCE:**

PARAMETERS	ASTM	UNIT	VELOCITY NANO PLUS (MINERAL)	
			15W-40	20W-50
Grade			15W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D445	cSt	112.8	177.9
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15.1	19.9
Viscosity Index	D2270	-	140	130
SP. Gravity @15°C/ 60°F	D4052	g/cm <sup>3</sup>	0.872	0.889
Flash Point (min)	D92	°C	234	236
Pour Point (max)	D97	°C	-33	-24
TBN	D2896	Mg KOH/g	10	10
CCS, (°C)	D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

**PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.