



AIR FILTER OIL

PRODUCT DESCRIPTION:

Air Filter Oil has been specially formulated for application to "wet type" foam air filters to four and two stroke engines. Through a carefully designed balance of selected base oils and additives, the product provides excellent performance in preventing airborne dirt and abrasive particles from passing through the fuel intake system into the combustion chamber.

APPLICATION:

Air Filter Oil is designed for use in all oiled foam elements.

DIRECTIONS FOR USE:

NOTE: Wear solvent resistant gloves when using Air Filter Oil.

Ensure the foam filter is clean. To clean, wash a dirty filter in solvent (for example, kerosene or distillate) to remove oil and dirt. Squeeze out any remaining solvent carefully, taking care not to damage the foam element. Service the foam air filter regularly in accordance with the manufacturers' instruction, and particularly when the unit has been used in dusty, dirty operating environments.

NOTE: If the filter is washed with a degreaser and then with water, remove as much water as possible by shaking or squeezing between an absorbent material or leaving to dry, before applying Air Filter Oil.

Do not apply or mix Air Filter Oil with any other fluid to the wet type foam air filters otherwise the efficiency of the product will be impaired.

FEATURES & BENEFITS:

- Developed to ensure excellent performance for motorcycle filters.
- Tested in both controlled field conditions and bench test procedures according to BSI 1701 (ISO 511).
- High filtering efficiency for extended filter and engine life.
- Maintains air flow for instant engine response and maximum power output.

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	Air Filter Oil
Appearance	-	-	Blue Tacky Oil
Flash Point, °C	D92	°C	40
Density@15°C/ 60°F	D4052	g/cm3	TBR

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.