



## **AVALANCHE DEXCOOL 50** **EXTENDED LIFE COOLANT/ ANTIFREEZE**

### **PRODUCT DESCRIPTION:**

Avalanche Dexcool 50 is a single phase ethylene glycol based extended life coolant for automotive engines. Avalanche Dexcool 50 meets GM 6277M – General Motors new extended life coolant specification.

### **APPLICATION:**

Avalanche Dexcool 50 is recommended for diesel and gasoline applications requiring nitrite, silicate and phosphate free extended life coolant.

### **FEATURES & BENEFITS:**

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump
- Prevents the buildup of deposits, keeping the cooling system clean
- Long life service product

### **PERFORMANCE LEVELS / MEETS OR EXCEEDS:**

GM 6277M/1825M/1899M, US FED A-A-870-A, CHRYSLER MS 9769, FORD WSS-M97B44-D2, VAG G-12, ASTM D4656

### **TYPICAL PERFORMANCE:**

PARAMETERS	ASTM	UNIT	AVALANCHE DEXCOOL 50
pH	D1278	cSt	8.1
Freezing Point	D1177	°C	-37
Boiling Point	D1120	cSt	110
Density at 15.5C	D4052	g/cm <sup>3</sup>	1.06

### **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### **HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### **PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### **STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.