



## CHF PLUS

### PRODUCT DESCRIPTION:

CHF Plus is a highly effective multi-purpose synthetic hydraulic fluid with ashless additives. It is specially developed for power steering, brake, suspension leveling and hydraulic suspension systems of modern cars. It can also be used in shock absorber, hydro-pneumatic suspension, traction and stability control systems.

### APPLICATION:

CHF Plus is recommended for the service re-fill or top-up of the power steering and suspension systems in many late model European manufactured prestige vehicles. It can also be used as a direct replacement for OEM LDS fluids or it is a ready replacement for OEM Pentosin CHF 11S and can also be used as a replacement for LHM+ type fluids creating less inventory for workshops. CHF Plus may also be used in the brake systems of certain vehicles, please check the vehicle handbook before use.

### FEATURES & BENEFITS

- Good flow rates of fluid at extremes of temperature
- Excellent lubricating properties
- High thermal stability
- Excellent protection against wear & corrosion
- Excellent compatibility with all kind of seals and hoses

### TYPICAL PERFORMANCE:

P PARAMETERS	CHF PLUS (Typical Specification)
MAN	M3289
MB	345.0
PENTOSIN	CHF 11S
Chrysler	MS-11655
FORD	M2C204-A
BMW	81 22 9 407 758
VW/SEAT/SKODA/AUDI	G 002 000 (TL 521 46), G 004 000
HYUNDAI/KIA	PSF-3/PSF-4
FIAT	9.55550-AG2/9.55550-AG3 VG 22
GM	89021185/ 89021186/ 1052884/ 993294
VOLVO	1161529

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.