



ENGINE FLUSH

PRODUCT DESCRIPTION:

Lubrex Engine Flush helps restore fuel economy, increase operating efficiency and reduce emissions in gasoline and diesel engines. Its powerful detergent based formula, cleans sludge and deposit build-up, promoting reduced oil consumption. Lubrex Engine Flush is safe on parts and can be easily disposed of with waste oil.

FEATURES & BENEFITS:

- Helps loosen sticky valves and rings, minimizing blow-by and reducing emissions
- Promotes lower operating temperatures through sludge removal
- Helps quiet lifter noise
- Does not attack common sealing materials
- Highly economical

APPLICATIONS:

Cleaning and flushing out the oil circuits of gasoline and diesel engines. The use of Lubrex Engine Flush is dependent on the degree of contamination of the oil circuit. Not suitable for use in motorbikes with wet clutches.

DIRECTIONS:

One 300 ml can is sufficient for up to 6 litres of oil. Add Lubrex Engine Flush to the motor oil at running temperature before changing the oil. After adding the product, allow the engine to idle for approximately 10 minutes. Then change the oil and the filter. Lubrex Engine Flush is compatible with all commercially available motor oils.

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ENGINE FLUSH
Kinematic Viscosity @ 104°F /40°C	ASTM D-445	cSt	<7
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.80
Flash Point (min)	ASTM D-93	°C	60
Pour Point (max)	ASTM D-97	°C	-45
Odor			Characteristic

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.