



FRICTO LITHIUM GREASE MP

PRODUCT DESCRIPTION:

Fricto Lithium MP is multi-purpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off-road equipments operating in wet, dusty and/or dry conditions.

APPLICATION:

Fricto Lithium MP is used for lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal. Pre-eminently suitable for passenger cars, light trucks and leisure vehicles applications. Always avoid contamination of the grease by dust and/or dirt when applying.

FEATURES & BENEFITS:

- Excellent mechanical stability avoiding ejection or loss of consistency during operation
- Excellent pumpability due to the low-temperature characteristics and smooth texture
- Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained

MEETS OR EXCEEDS THE REQUIREMENTS OF:

- ISO 6743-9: L-XBCEA 2
- DIN 51 502: K2K -25

TYPICAL PROPERTIES:

TEST	ASTM METHOD	FRICTO LITHIUM MP		
		NLGI 00	NLGI 2	NLGI 3
Thickener Type	-	Lithium	Lithium	Lithium
Color	-	Light Brown	Light Brown	Light Brown
Texture	-	Semi Fluid	Smooth	Smooth
Worked Penetration @ 25°C, 60 Strokes	D-217	415	280	235
Dropping Point, °C	D-2265	180	190	190
Base Oil Viscosity @ 40°C, cSt	D-445	150	150	150
Operating Temperature Range, °C	-	-25 to 120	-25 to 120	-25 to 120

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.