



MARINE SO 630, SO 640

PRODUCT DESCRIPTION:

Marine SO 630 and SO 640 are premium quality multipurpose system oils designed, primarily for low speed, crosshead marine diesel engines operating on residual fuels. They are alkaline oils giving the highest levels of protection in a wide variety of engine and shipboard applications.

APPLICATION:

- Crankcase System of low speed, crosshead, and marine diesel engines operating on residual fuel
- Main and Auxiliary trunk piston diesel engines burning distillate fuels
- Turbochargers
- Geared transmission
- Oil Lubricated Stern tubes
- Variable Pitch propellers
- Deck Machinery
- Other ancillary equipment requiring an SAE 30 or 40 Oil

FEATURES & BENEFITS:

- Excellent thermal and oxidation stability
- Excellent dispensancy
- Good Alkalinity
- Good water shedding properties
- Excellent resistance to corrosion

MEETS OEMs:

- MAN
- Wartsila
- MHI

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	Marine SO 630	Marine SO 640
Grade			30	40
Kinematic Viscosity @ 104°F/40°C	ASTM D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F/100°C	ASTM D445	cSt	11.0	14.5
Viscosity Index	ASTM D2270	-	95	95
Density@ 60°F	ASTM D4052	g/cm ³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-9	-9

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.