



MOMENTA NANO PLUS

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Momenta Nano Plus is a synthetic, high performance heavy-duty diesel engine oil that helps extend engine life and improve fuel economy in modern diesel engines operating in severe conditions. Momenta Nano Plus meets the API CJ-4 specification utilizing state-of-the-art technology to deliver exceptional performance in modern low emission engines, including those with Exhaust Gas Recirculation (EGR), After-Treatment Systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's).

APPLICATION:

Momenta Nano Plus is recommended for use in 4-stroke diesel engines, including modern low emission engines with Exhaust Gas Recirculation (EGR), After-Treatment systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's). Recommended for on-highway engines operating in both high speed / high load and stop-and-go conditions, and Off-highway engines operating in severe low speed/heavy load conditions. Also suitable for high performance gasoline engines and mixed fleets.

SUITABLE FOR:



FEATURES & BENEFITS:

- Prevents premature DPF plugging and shortened maintenance intervals
- Minimizes piston and combustion chamber deposits
- Fights Sludge and Varnish
- Excellent against engine wear due to soot formation
- Excellent oxidation, foam, and corrosion inhibition
- Provides faster, and safe starts during extreme temperatures and increases thermal and oxidation stability at extreme high temperatures
- Extended engine life

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

This product is recommended for use in applications requiring:

- API CJ-4/SN
- ACEA E9
- MB 228.31
- Caterpillar ECF-3
- MAN M3477/3575
- VOLVO VDS-4
- Renault RLD-3
- DDC 93K218
- Mack EO-O PP
- Cummins CES 20081
- DEUTZ DQC III-10 LA
- FORD WSS-M2C171-F1


TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOMENTA NANO PLUS (FULLY SYNTHETIC)			
			0W-30	0W-40	5W-30	5W-40
Grade						
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	67.1	87.5	68.45	91.65
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.85	14.9	11.8	15
Viscosity Index	D-2270	-	175	180	170	173
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.845	0.845	0.86	0.86
Flash Point (min)	D-92	°C	234	230	234	232
Pour Point (max)	D-97	°C	-42	-42	-42	-42
TBN	D-2896	Mg KOH/g	9.9	9.9	9.9	9.9
CCS, (°C)	D-5293	m.Pa.S	6200 (-35°C)	6200 (-35°C)	6600 (-30°C)	6600 (-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.