



## MOMENTA RX MINERAL

### PRODUCT DESCRIPTION:

Momenta RX is a mineral multi-grade diesel engine oil recommended for the lubrication of diesel engines and naturally aspirated gasoline engines used in commercial and passenger vehicles operating under mild driving conditions.

### APPLICATION:

Recommended for the lubrication of diesel / gasoline engines used in trucks and passenger cars operating under mild driving conditions. It can also be used in agriculture equipment, medium-duty trucking, off-road vehicles, construction and quarrying, and certain transmission and mobile hydraulic systems where use of monograde engine oils is recommended by the equipment manufacturer.

### SUITABLE FOR:



### FEATURES & BENEFITS:

- Good protection against rust and corrosion
- Thermal and oxidation stability
- Controls sludge buildup and deposits
- Long equipment life and reduced maintenance cost.

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

This product is recommended for use in applications requiring:

- API CC/SC
- MIL-L-2104B

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOMENTA RX ( MINERAL )				
			15W-40	20W-50	20W-60	40	50
Grade			15W-40	20W-50	20W-60	40	50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	116.4	181.65	201.05	151.4	214.15
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.45	20.3	24.2	15.5	20.2
Viscosity Index	D-2270	-	140	131	150	105	110
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.882	0.891	0.887	0.895	0.896
Flash Point (min)	D-92	°C	236	236	230	242	246
Pour Point (max)	D-97	°C	-33	-24	-24	-15	-15
TBN	D-2896	Mg KOH/g	3.5	3.5	3.5	3.5	3.5
CCS, (°C)	D-5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)	<9500 (-15°C)	-	-



**LUBREX**  
Innovative Fluid Engineering

**HDDO**

## Technical Data Sheet



### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.