



**MOMENTA RX9**  
**FULLY SYNTHETIC**

**PRODUCT DESCRIPTION:**

Momenta RX9 combines a high quality synthetic base stock with a proprietary, balanced additive system having a combination of metallic detergents, dispersants and multi-purpose inhibitors. This oil assures superior control of oil thickening caused by soot buildup and high temperature oxidation. It also provides outstanding resistance to varnish deposits and corrosion.

**APPLICATION:**

These heavy-duty engine oils are recommended for all types of diesel and gasoline engines where the manufacturer specifies the API service CH-4/SJ. They are especially suited for use in low temperature environments where extreme pumpability properties are required. These Oils are also suitable for on-road and off-road applications, including equipment that are exposed to extreme low temperature operations. This oil is suitable for use in moderate to high sulphur content fuel.

**SUITABLE FOR:**



**FEATURES & BENEFITS:**

- Improved oxidation stability to minimize deposit formation
- Higher TBN to extend protection from acids caused by combustion
- Better protection against valve train wear
- Improved low temperature performance
- Potential fuel economy improvement compared to conventional CH-4 heavy-duty engine oils

**PERFORMANCE LEVELS / MEETS OR EXCEEDS:**

This product is recommended for use in applications requiring:
• <b>API CH-4/SJ</b>
• <b>MB 228.3</b>
• <b>MAN 3275</b>
• <b>ACEA E7, A3/B3/B4</b>
• <b>VOLVO VDS-2</b>
• <b>Renault RLD-2</b>
• <b>MTU Type 2</b>
• <b>JASO DH1</b>
• <b>Mack EO-M/EO-L</b>
• <b>Cummins CES 20076</b>
• <b>DFS 93K215</b>
• <b>DQC III-10</b>


**TYPICAL PERFORMANCE:**

PARAMETERS	ASTM	UNIT	MOMENTA RX9 ( FULLY SYNTHETIC)			
			0W-30	0W-40	5W-30	5W-40
Grade						
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	68.55	90.05	68.85	91.65
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	12.1	15.3	11.9	15
Viscosity Index	D-2270	-	176	181	171	173
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.846	0.846	0.858	0.859
Flash Point (min)	D-92	°C	234	230	234	232
Pour Point (max)	D-97	°C	-42	-42	-42	-42
TBN	D-2896	Mg KOH/g	10.5	10.5	10.5	10.5
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

**PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.