



OPTIMUS LITHIUM COMPLEX GREASE

PRODUCT DESCRIPTION:

Optimus Lithium Complex are extended service lithium complex greases intended for a wide variety of applications and severe operating conditions. They are formulated to provide excellent high-temperature performance with superb adhesion, structural stability and resistance to water contamination. These greases have a high level of chemical stability and offer excellent protection against rust and corrosion.

APPLICATION:

- Optimus Lithium Complex EP-00 and EP-0 are used in a wide range of equipment including industrial, automotive, construction and marine applications. Softer, high-temperature greases recommended for centralized grease application systems, gear lubrication, and where extreme-cold-temperature pumpability is important
- Optimus Lithium Complex EP-1 is recommended for use in industrial and marine applications, chassis components and farm equipment. It provides excellent low-temperature performance
- Optimus Lithium Complex EP-2 is recommended for industrial and marine applications, chassis components and farm equipment. Its sticky formulation stays in applications longer
- Optimus Lithium Complex EP-3 is recommended for applications where good high temperature and anti-leakage properties are required. Especially recommended for severe truck wheel bearing applications or for rolling element bearings subject to vibration, or where higher speeds require a grease with higher consistency to provide channelling characteristics

FEATURES & BENEFITS:

- Superb resistance to water washout and spray-off
- Highly adhesive and cohesive structure
- Excellent rust and corrosion resistance
- Very good resistance to thermal, oxidative and structural degradation at high temperature
- Very good anti-wear and EP performance
- Broad multi-purpose application

MEETS OR EXCEEDS THE REQUIREMENTS OF:	NLGI 00	NLGI 0	NLGI 1	NLGI 2	NLGI 3
DIN 51825: (2004-06)	-	-	KP1N-20	KP2N-20	-
Fives Cincinnati	-	P-79	P-72	P-64	-

TYPICAL PROPERTIES:

TEST	ASTM METHOD	OPTIMUS LITHIUM COMPLEX				
		NLGI 00	NLGI 0	NLGI 1	NLGI 2	NLGI 3
Thickener Type		Lithium Complex				
Color		Dark Blue				
Texture		Smooth				
Worked Penetration @ 25°C, 60 Strokes	D-217	415	370	325	280	235
Dropping Point, °C	D-2265	-	250	260	260	260
Timken EP Test, OK Load, lbs	D-2509	40	40	40	40	40
4-Ball Wear, Scar, mm	D-2266	0.5	0.5	0.5	0.5	0.5
4-Ball Weld Load, Kg	D-2596	315	315	315	315	315
Base Oil Viscosity @ 40°C, cSt	D-445	220	220	220	220	220
Operating Temperature Range, °C		-30 to 140	-30 to 140	-30 to 140	-30 to 140	-30 to 140



HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.