



## POWER STEERING FLUID

Power Steering Fluid is a premium fully synthetic oil specially designed for use in power steering and suspension units. It contains a unique combination of anti-shudder additives, dispersants and seal swell additives along with a specialized synthetic base oil to offer maximum wear protection, long service life and minimization of viscosity loss.

### APPLICATION:

Power Steering Fluid is primarily designed and recommended for use in the power steering units of all Honda motor vehicles as well as Rover models 416i, 825 and 827 that use Honda power steering components. It may also be used in high performance applications in other vehicles such as Ford Tickford series, AU, BA & BF XR, FPV & Territory SX-SY series vehicles. The synthetic base oils and higher viscosity help to reduce pump wear and maintain steering feel where extra heat and load is expected in these applications.

### FEATURES & BENEFITS:

- Correct viscosity for Honda Power Steering units
- Compatible with OEM fluid
- Reduces power steering shudder (noise & chatter)
- Extends seal and hose life
- Multiple-use power steering & suspension
- Long Service life
- Protects against rust and corrosion

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Ford M2C134-C
- Ford M2C134-D
- Honda PSF-II
- Honda PSF-S
- Honda PSF-V

### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	POWER STEERING FLUID
KV@ 104°F /40°C	D7042	cSt	71.35
KV @ 212°F /100°C	D7042	cSt	11.7
Viscosity Index	D2270	-	160
SP. Gravity @15°C	D4052	g/cm3	0.860
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.