



RACE 4T CLASSIC SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

Race 4T Classic is a multi-grade motor oil for four-stroke engines of motorcycles, scooters and mopeds. RACE 4T CLASSIC is blended by using high-quality base oils and the balanced additive system of quality additive manufacturers. It has improved detergency, antiwear, anti-foam properties and offers high resistance to oxidation and corrosion.

APPLICATION:

RACE 4T Classic is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SF performance level, and also for motorbikes transmissions and clutches, which need lubrication by motor oils.

FEATURES & BENEFITS:

- Maximum engine power
- Excellent gear protection
- Outstanding wear protection
- Outstanding shear and oxidation resistance
- Better clutch "feeling"
- Excellent low temperature fluidity

PERFORMANCE LEVELS: Meets and Exceeds:

- API SF

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	RACE 4T CLASSIC						
			10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Grade			10W-30	10W-40	10W-50	15W-40	15W-50	20W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	73.7	101.4	131.5	108.2	149.7	123.9	176.5
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1	19.5	15	19.5	15	20
Viscosity Index	D2270	-	154	157	170	145	150	125	132
TBN	D8698	MgKOH/g	6	6	6	6	6	6	6
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	0.875	0.879	0.875	0.885	0.885	0.890	0.889
Flash Point (min)	D92	°C	224	224	224	222	222	236	234
Pour Point (max)	D97	°C	-39	-39	-39	-33	-30	-24	-24

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.



RACE 4T SYNTH HD 20W-50 SYNTHETIC

PRODUCT DESCRIPTION:

Race 4T Synth HD 20W-50 is a fully synthetic motorcycle oil tailored for use in air and water-cooled four-stroke motorbike engines and especially suitable for Harley Davidsons. Selected base oils and high-quality additive components ensure optimum lubrication, outstanding engine cleanliness and excellent friction in all operating conditions. It is exceptionally well-suited for use with or without a wet clutch.

APPLICATION:

Race 4T Synth is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SN performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

SUITABLE FOR:

FEATURES & BENEFITS:

- Stable to ageing and viscosity
- Excellent wear resistance
- Outstanding corrosion protection
- High engine cleanliness
- Outstanding high temperature stability

PERFORMANCE LEVELS: Meets and Exceeds:

- API SN
- JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	RACE 4T SYNTH HD 20W-50
Grade			20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	138.3
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	19.5
Viscosity Index	D2270	-	162
TBN	D8698	MgKOH/g	7
SP. Gravity @15°C/ 60°F	D4052	g/cm3	0.850
Flash Point (min)	D92	°C	240
Pour Point (max)	D97	°C	-39

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.