



## SHIFT SYNTH EP 75W-90 EXTREME PRESSURE AUTOMOTIVE GEAR OIL

### PRODUCT DESCRIPTION:

Shift Synth EP 75W-90 is a fully synthetic lubricant used for drive axles on General Motors vehicles where oil to GM specifications 9986115 is required.

### APPLICATION:

Shift Synth EP 75W-90 is recommended as service-fill lubricant for drive axles on General Motors vehicles requiring the product meeting GM 9986115 specifications.

### FEATURES & BENEFITS

- Excellent viscosity/temperature properties
- Outstanding axle wear protection.
- outstanding corrosion protection
- excellent wear resistance
- Improved shear stability for a stable viscosity during use
- excellent resistance to aging

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- GM 9986115

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SHIFT SYNTH EP
			75W-90
KV@ 104°F /40°C	D7042	cSt	TBR
KV@212°F /100°C	D7042	cSt	14.6
Viscosity Index (min)	D2270	-	140
SP. Gravity @15°C	D4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-45

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.