



## TORQUE EAL

### PRODUCT DESCRIPTION:

To reduce the environmental impact and to protect the environment from accidental oil spills, Lubrex has developed a range of synthetic oleochemical esters based biodegradable hydraulic oil products. The Torque EAL range of biodegradable hydraulic oils are readily biodegradable lubricants which meet very strict criteria and requirements in terms of biodegradability and toxicity.

### APPLICATION:

Torque EAL biodegradable hydraulic oils are designed for use in high pressure industrial, agriculture, marine, construction and mobile applications that are operated in environmentally sensitive areas. Use in applications that require any of the following:

- Pw1 Ultimate Biodegradability (ASTM D5864)
- OECD 301B Readily Biodegradable
- Vessel General Permit (VGM) Compliant
- EN 16807: European Standard

### FEATURES & BENEFITS:

- Excellent biodegradability (ultimately biodegradable)
- Low aquatic toxicity
- Good antiwear and anticorrosion performance
- Non-bio accumulation
- Very high renewability content
- Excellent low-temperature flow properties
- Excellent oxidation stability
- Good SRE-NBR seal compatibility

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	TORQUE EAL		
ISO VG			46	68	100
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	46	68	100
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	8	10.8	14.5
Viscosity Index	ASTM D-2270	-	148	149	150
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.92	0.92	0.93
Flash Point (min)	ASTM D-92	°C	280	284	286
Pour Point (max)	ASTM D-97	°C	-44	-42	-40
Copper Strip Corrosion 3 hours @ 100° C	ASTM D-130	-	1A	1A	1A
Rust Characteristics	ASTM D-665A&B	-	PASS	PASS	PASS
Foam Sequence I, II, III	ASTM - D892	ml	0/0, 0/0, 0/0	0/0, 0/0, 0/0	0/0, 0/0, 0/0
Demulsibility, 54°C, 3ml emulsion	ASTM - D1401	minutes	40/40/0 (15)	40/40/0 (20)	40/40/0 (20)



**LUBREX**  
Innovative Fluid Engineering

## INDUSTRIAL HYDRAULIC FLUID

### Technical Data Sheet



#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.