



## VELOCITY CNG PLUS MINERAL

### PRODUCT DESCRIPTION:

Velocity CNG Plus is a high performance heavy-duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck, bus engines and small to medium size CNG generators. It provides excellent performance in the challenging operating environment presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability.

### APPLICATION:

- LNG/CNG Linehaul truck service
- LNG/CNG Delivery truck service
- LNG/CNG Waste truck service
- LNG/CNG Cement truck service
- LNG/CNG Oil Field truck service
- CNG Municipal Bus Service
- Small to Medium Size CNG Generators
- Off Road Equipment

### FEATURES & BENEFITS:

- Good piston and engine cleanliness
- Reduced levels of "ash" containing additives to control deposit formation
- Excellent tappet and liner wear performance in alternative fuel engines
- Delivers long drain performance protection despite higher stress of CNG combustion

### PERFORMANCE LEVELS: Meets and Exceeds:

- API CF
- Cummins: CES 20074
- Detroit Diesel: DDC 93K216

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY CNG PLUS	
			15W40	20W50
Grade			15W40	20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	108	170
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	14.8	19.5
Viscosity Index	ASTM D-2270	-	142	131
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.875	0.880
Flash Point (min)	ASTM D-92	°C	238	242
Pour Point (max)	ASTM D-97	°C	-30	-24
TBN	ASTM D-2896	Mg KOH/g	6.4	6.4
CCS, (°C)	ASTM D-5293	m.Pa.S	6500 (-20)	9000 (-15)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.