



VELOCITY GX3 MINERAL

PRODUCT DESCRIPTION:

Velocity GX3 is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.

APPLICATION:

Gasoline and light-duty diesel engines found in passenger cars, farm and construction equipment, stationary diesel engines and four-stroke engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SF/CD
- MIL-L-2104A

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY GX3 (MINERAL)				
			40	50	15W-40	20W-50	20W-60
Grade			40	50	15W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	150	212.5	110.2	172.95	243.2
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	14.5	19.5	15.2	19.5	25.7
Viscosity Index	D-2270	-	95	105	145	130	136
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.898	0.898	0.885	0.890	0.889
Flash Point (min)	D-92	°C	250	254	224	236	232
Pour Point (max)	D-97	°C	-15	-15	-30	-24	-24
TBN	D-2896	Mg KOH/g	6	6	6	6	6
CCS, (°C)	D-5293	m.Pa.S	N/A	N/A	<6800 (-20°C)	<9100 (-15°C)	<9200 (-15°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.