



## VELOCITY GX5 MINERAL

### PRODUCT DESCRIPTION:

Velocity GX5 mineral engine oil is a superior quality multi grade oil formulated with highly refined base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city.

### APPLICATION:

Gasoline and light-duty diesel engines found in passenger cars, farm and construction equipment, stationary diesel engines and four-stroke engines. It can be comfortably used in mixed fleet.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SG/CF

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY GX5 (MINERAL)			
			15W-40	20W-50	20W-60	50
Grade			15W-40	20W-50	20W-60	50
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	110.0	170.3	210.0	220.3
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	15.0	19.6	25.5	19.5
Viscosity Index	D-2270	-	139	133	138	100
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.885	0.890	0.889	0.889
Flash Point (min)	D-92	°C	224	236	230	260
Pour Point (max)	D-97	°C	-30	-24	-24	-15
TBN	D-2896	Mg KOH/g	6.5	6.5	6.5	6.5
CCS, (°C)	D-5293	m.Pa.S	<6800 (-20°C)	<9100 (-15°C)	<9300 (-15°C)	--

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>TM</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.