



## VELOCITY GX5 SEMI SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity GX5 is semi synthetic oil for gasoline and diesel engines having high ageing resistance which effectively reduces carbon formation and high-temperature lacquer formation. It provides safe lubrication of the engine components. This oil contains low-ash additives which allows to prolong the endurance of the catalyst.

### APPLICATION:

Recommended for gasoline and light-duty diesel engines found in passenger cars, agriculture and construction equipment, stationary diesel engines and four-stroke engines. It can be comfortably used in mixed fleet.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SG/CF

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY GX5	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	76.2	100.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.9	14.90
Viscosity Index	ASTM D-2270	-	152	156
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.869	0.876
Flash Point (min)	ASTM D-92	°C	230	230
Pour Point (max)	ASTM D-97	°C	-36	-36
TBN	ASTM D-2896	Mg KOH/g	6.5	6.5
CCS, (°C)	ASTM D-5293	m.Pa.S	<6600 (-25°C)	<6700 (-25°C)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.