



VELOCITY GX7 FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Velocity GX7 is a superior quality fully synthetic engine oil formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the buildup of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

APPLICATION:

Recommended for all naturally aspirated, fuel injected, turbo-charged and multi-valve passenger car engines without particulate filters.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Outstanding wear and friction protection
- Excellent detergency and dispersancy
- Easy start at low temperatures
- Excellent protection against sludge and varnish buildUp

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-30	5W-40
API	SJ/CF	SJ/CF
ACEA	A1/B1	A3/B3
ILSAC	GF-2	GF-2
FORD	WSS-M2C-913A/913B	-

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY GX7	
			5W-30	5W-40
SAE Grades				
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.1	14.5
Viscosity Index (min)	D2270	-	160	160
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39
TBN	D2896	mg KOH/g	6	6
CCS	D5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.