



VELOCITY NANO RX SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Velocity Nano RX is a semi synthetic lubricant fortified with proven metallo-organic anti-wear additive system which protects engines under all operating conditions by providing excellent wear control in even the most sophisticated valve train mechanisms, including those with variable valve timing. It has been expertly engineered to help deliver superior cleaning power, wear protection and outstanding performance. It helps resist degradation between oil changes, extending the time and mileage interval between oil changes.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Helps reduce engine wear and corrosion
- Fully compatible with all emission control devices and all gasoline grades

PERFORMANCE LEVELS: Meets and Exceeds:

- API SN/CF
- ACEA A3/B3
- MB 229.3
- Renault RN0700
- Renault RN0710
- VW 502 00
- VW 505 00

API LICENSE:

- SAE 5W30
- SAE 5W40



TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY NANO RX (SEMI SYNTHETIC)	
			5W-30	5W-40
Grade			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	66.3	90.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	11.5	15
Viscosity Index	ASTM D-2270	-	170	176
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.848	0.851
Flash Point (min)	ASTM D-92	°C	232	232
Pour Point (max)	ASTM D-97	°C	-42	-42
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	<6600 (-30°C)	<6600 (-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net



LUBREX
Innovative Fluid Engineering

PCMO

Technical Data Sheet



HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.