



VELOCITY NANO SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Velocity Nano is an advanced semi synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. This oil is designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, light truck gasoline engines, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- Enables fast and easy start in extreme temperature conditions
- Particularly recommended for urban driving
- Oil film able to withstand high operating temperatures
- Protects engines against deposits
- Standard drain interval

PERFORMANCE LEVELS: Meets and Exceeds:

- API SM/CF
- ACEA A3/B3
- VW 501.01 / 505.00
- RN 700, RN 710
- MB 229.3

API LICENSE:

- SAE 10W-30
- SAE 10W-40



TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY NANO (SEMI SYNTHETIC)	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	63.3	100.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	10.4	15.1
Viscosity Index	ASTM D-2270	-	154	159
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.876	0.876
Flash Point (min)	ASTM D-92	°C	236	236
Pour Point (max)	ASTM D-97	°C	-39	-42
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	<7000 (-25°C)	<6600 (-30°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net



HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.