



VELOCITY NANO XTL FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Velocity Nano XTL is a very high performance, fully synthetic MID SAPS lubricant for gasoline and diesel engines, including the ones complying with ACEA C2/C3 standard. Velocity Nano XTL is formulated to reduce pollutant emissions, such as HC, NOx, CO and particles and to protect and ensure longevity of after-treatment antipollution systems, such as Particulate Filters (GPF, DPF) and Three-Way Catalysts. Synthetic base oils together with the latest additive technology, guarantee a motor oil that provides exceptional protection against wear and reduces oil and fuel consumption.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ACEA industry specifications for petrol engine oils, as well as the requirements of many major American and European engine manufacturers. Suitable for use in both gasoline and diesel passenger cars and light commercial vehicles.

SUITABLE FOR:



FEATURES & BENEFITS:

- Excellent engine cleanliness
- Excellent cold flow properties
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices
- Helps protect engine against wear and corrosion
- Allows fuel consumption reduction and therefore minimizes green house gases emission

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-40	5W-30
API	SN PLUS/ SP	SN PLUS/ SP
ACEA 2016	C3	C3/C2
BMW	LL-04	LL-04
MB	229.51/ 229.52	229.51/ 229.52
OPEL	OV 040 1547	OV 040 1547
RENAULT	RN0700/RN0710	RN0700/RN0710


TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	VELOCITY NANO XTL (TYPICAL SPECIFICATION)	
			5W-40	5W-30
Grade				
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	77.2	65.4
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	13.5	11.8
Viscosity Index	D-2270	-	180	179
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.859	0.860
Flash Point (min)	D-92	°C	224	220
Pour Point (max)	D-97	°C	-42	-42
TBN	D-2896	Mg KOH/g	9	9
CCS, (°C)	D-5293	m.Pa.S	<6600	<6600

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.