



## VELOCITY SPECIFIC LL-01 FE 0W-30

### Passenger Car Motor Oil

#### PRODUCT DESCRIPTION:

Velocity Specific LL-01 FE 5W-30 is a premium quality lubricant which is particularly resistant at high temperatures to allow better control of oil consumption and to reduce wear due to its excellent lubricating properties, while providing significant fuel economy. Provides excellent oil flow, instant oil pressure, faster engine revs up and faster engine warm-up.

Velocity Specific LL-01 FE 5W-30 helps reduce fuel consumption thus reducing green house gas (CO<sub>2</sub>) emissions to protect the environment.

#### APPLICATION:

Velocity Specific LL-01 0W-30 is specially designed for BMW and MINI vehicles, fitted with gasoline engines meeting Euro 4, 5 and 6 emission standards, requiring a "Fuel Economy" engine oil meeting BMW Long-Life 01 FE specifications.

#### FEATURES & BENEFITS

- Excellent low temperature flow when cold starting, helping to instantly protect vital components
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine
- Excellent engine cleanliness and durability which reduces emissions and provides extended drain capability
- Delivers instant protection under hot or cold conditions

#### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

GRADES	0W-30
ACEA	A5/B5
BMW	LL-01 FE

#### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	0W-30
Kinematic Viscosity @40C	D445	cSt	63.3
Kinematic Viscosity @40C	D445	cSt	10.7
Viscosity Index	D2270	-	161
TBN	D2896	MgKOH/g	11
Pour Point	D97	°C	-42
Density at °15C	D4052	g/ml	0.855



**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

**PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.