



## MOTO PRO PRE-MIX 2T

### FULLY SYNTHETIC LOW SMOKE OIL

#### PRODUCT DESCRIPTION:

Moto Pro Pre-mix 2T engine oil is a fully synthetic lubricant which is designed to provide excellent performance in two-stroke engines. Its composition is perfectly compatible with lead-free fuels. This is a high technology product, combining a perfect balance of premium synthetic base stocks and the latest additives' technology. It is specially formulated for use in oil injected as well as pre-mixed gasoline/oil lubricated engines. Its additive package offers enhanced detergents to maintain a clean-burning, low smoke engine and the lubrication to protect it no matter how hard you ride.

#### APPLICATION:

Moto Pro Pre-mix 2T engine oil is intended for use in two-stroke, air cooled engines. It is also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended.

#### FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke.
- Thermal and oxidation stability.
- Specially formulated to avoid spark plug fouling.
- Perfectly adapted to unleaded fuel.
- Protection against pre-ignition problems.

#### PERFORMANCE LEVEL: Meets and Exceeds:

- API TC
- JASO FD
- ISO EGD

#### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOTO PRO 2-CYCLE ENGINE OIL
<b>Grade</b>			<b>20</b>
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	42
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7.7
Viscosity Index	ASTM D-2270	-	154
Flash Point (min)	ASTM D-92	°C	100
Pour Point (max)	ASTM D-97	°C	-42

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.