



VELOCITY ACE 5W-30 SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Velocity ACE is a premium quality semi synthetic engine oils are advanced passenger car motor oil specially developed for the most modern high output turbo- charged gasoline engines in passenger cars, sport utility vehicles, vans and light-duty trucks. This oil is engineered to provide the highest levels of engine protection available. It contain ultra-pure base oils and a technologically advanced additive system which provides improved oxidation resistance, improved deposit protection, better wear protection, excellent low temperature performance and enhanced fuel economy.

APPLICATION:

Recommended to be used in North American, European & Japanese high output gasoline engines in passenger cars, sport utility vehicles, vans, and light-duty trucks where API SP, SN Plus, ILSAC GF-6A and / or API SN, API SM, API SL quality oils are specified, passenger cars and light-duty vehicles running on gasoline and ethanol-containing fuels up to E85, suitable for modern turbo- charged direct injection gasoline engines where LSPI protection is required.

FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions
- Special cleaning additive to help prevent the formation of sludge and harmful deposits
- Optimal engine operating temperature, owing to thermal control formula
- Limits formation of deposits on the most loaded engine parts
- Provides safe operation of catalytic exhaust converters
- Resistant to extreme thermal load, due to high quality of base oil
- Enables fast and easy start in extreme temperature conditions
- Extra cleaning performance

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API SP (RC) / SN PLUS (RC)
- ILSAC GF-6A
- GM DEXOS1 GEN2
- CHRYSLER MS6395
- FORD 946-B1/961-A

API LICENSE:

- SAE 5W-30



TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY ACE
			5W-30
KV@104°F /40°C	D7042	cSt	TBR
KV@212°F /100°C	D7042	cSt	10.2
Viscosity Index (min)	D2270	-	160
SP.Gravity@15°C	D4052	g/cm ³	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-39
TBN	D2896	mg KOH/g	7
CCS	D5293	m.Pa.S	<6600 (-30°C)

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.