



OPTIMUS L 220-EP

PRODUCT DESCRIPTION:

Optimus L-220 EP is a multi-purpose, extreme-pressure grease based on lithium 12-Hydroxystearate soap thickener and high-quality mineral base oil. This grease contains extreme pressure and other proven additives to enhance the performance in a wide range of applications. It is specifically recommended for steel mill, heavy-duty plain and rolling element bearings operating under severe conditions including shock loading and wet environments, gear box application where semi fluid grease is required and for centralized chassis lubrication systems.

APPLICATIONS

Optimus L-220 EP grease is specifically recommended for steel mill, heavy-duty plain and rolling element bearings operating under severe conditions including shock loading and wet environments, gear box application where semi fluid grease is required and for centralized chassis lubrication systems.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 130°C
- Excellent anti-wear and extreme pressure properties
- Excellent mechanical stability
- Good resistance to water-washout
- Excellent oxidation stability

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
		00	0	1
NLGI Grade	-	00	0	1
Thickener Type	-	Lithium Soap	Lithium Soap	Lithium Soap
Appearance	Visual	Smooth & Homogenous		
Color	Visual	Yellow to Light Brown		
Base Oil	-	Mineral	Mineral	Mineral
Work Penetration @25°C	ASTM D217	400-430	355-385	310-340
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b	1b	1b
Dropping Point °C, Min	ASTM D2265	N/A	190	190
Four Ball Weld Load Kgf, Min	IP239	250	250	250
Four Ball Wear Scar Dia, mm, Max	ASTM D2266	0.6	0.6	0.6
Operating Temperature Range, °C	INTERNAL	-20 to 130		
Base Oil Viscosity @40°C (Cst)	ASTM D445	220	220	220

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.