



## OPTIMUS ND 460

### PRODUCT DESCRIPTION:

Optimus ND 460 is made from Bentone clay, highly refined heavy base oil, anti-oxidant and anti-rust additives. It is resistant to water.

### APPLICATIONS

Optimus ND 46 grease is suitable for use within a very wide temperature range and especially at elevated temperatures for both industrial and automotive applications. The all-round properties make it suitable for various types of bearings, including temperature peaks up to 160°C.

### PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 160°C
- Non-melting thickener keeps consistency at high temperature
- Good water resistance properties
- Good oxidation and thermal stability
- Suitable for heavy and shock loading capabilities
- Good corrosion and rust protection

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Bentone Clay
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Brown
Work Penetration @25°C	ASTM D217	265-295
Dropping Point °C, Min	ASTM D2265	Non drop
Operating Temperature Range °C	INTERNAL	-20 to 160
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.