



## OPTIMUS P&B

### PRODUCT DESCRIPTION:

Optimus P&B grease is a well-known, multi-purpose lithium grease. The grease allows the presence of very fine-grade graphite which will fill surfaces and distribute the load evenly preventing further wear and tear. It is suitable for the lubrication of various industrial, agricultural, and earth-moving equipment applications.

### APPLICATIONS

Pin & Bush grease is suitable for the lubrication of various industrial, agricultural, and earth-moving equipment applications.

### PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 130°C
- High level of lubricating solids that keeps working surfaces apart and substantially extends component life
- Being fully resistant to the wet environment extends the life of the lubricant and protects components from corrosion
- Adhesion improves provide increased lasting protection

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	2	3
Thickener Type	-	Lithium Soap	Lithium Soap
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Gray/ Black	Gray / Black
Dry Lubricant	-	Graphite	Graphite
Work Penetration @25°C	ASTM D217	265-295	220-250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b	1b
Dropping Point °C, Min	ASTM D2265	220	220
Water Washout Resistance %Wt @79°C	ASTM D1264	max 10	max 10
Four Ball Weld Load, Kgf, Min	ASTM D2596	250	250
Operating Temperature Range °C	INTERNAL	-20 to 130	
Base Oil Viscosity @40°C (Cst)	ASTM D445	180	180

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.