



OPTIMUS PU 460-SYN

PRODUCT DESCRIPTION:

Optimus PU 460 Syn is a synthetic, high-performance, and long life product suitable for fill-for-life applications in wide range of industrial applications. This grease is based on synthetic, high-viscosity base stock engineered with performance additives resulting in an outstanding long life, high-performance grease. The product has also excellent water resistance and water washout characteristics. It is recommended for steel, paper, wind power applications as well as heavy duty slow moving plain and rolling element bearings operating in severe environments.

APPLICATIONS

Optimus PU 460 Syn grease is recommended for steel, paper, wind power applications as well as heavy duty slow moving plain and rolling element bearings operating in severe environments.

PRODUCT ADVANTAGES

- The operating temperature range is -30°C to 150°C
- Outstanding high-temperature oxidation stability
- Excellent extreme pressure properties
- High dropping point
- Effective corrosion protection
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	ASTM D217	1.5	2
Thickener Type	-	Di- Urea	Di- Urea
Base Oil Type	-	Fully Synthetic	Fully Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Light Brown	Light Brown
Work Penetration, 60 Strokes, 0.1 mm	ASTM D217	305	265-295
Dropping Point °C, Min	ASTM D2265	250	250
Cu Corrosion	ASTM D4048	1b	1b
Oxidation Stability, Drop In Pressure, Psi	ASTM D942	max 5	max 5
Oil Separation, % Wt.	ASTM D6184	max 3	max 3
Operating Temperature Range °C	INTERNAL	-30 to 150	
Base Oil Viscosity @40°C (Cst)	ASTM D445	460	460

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.