



VELOCITY GX9 MINERAL

PRODUCT DESCRIPTION:

Velocity GX9 is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbo-charged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.

APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

API LICENSE:

• SAE 20W50



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

| SAE GRADES | 15W-40 | 20W-50 | 20W-60 |
|------------|----------------|--------------|--------------|
| API | SL/CF | SL/CF | SL/CF |
| ACEA | A3/B3 | A3/B3 | A3/B3 |
| JASO | MA2 | MA2 | MA2 |
| RENAULT | RN0700/ RN0710 | RN 0700/0710 | - |
| VW | 501.01 / 505 | 501.01 / 505 | 501.01 / 505 |

TYPICAL PERFORMANCE:

| PARAMETERS | ASTM | UNIT | VELOCITY GX9 (MINERAL) | | | |
|-------------------------------------|-------|-------------------|------------------------|--------------|--------------|----------------|
| | | | 15W-40 | 20W-50 | 20W-60 | 25W-60 |
| SAE Grades | | | | | | |
| Kinematic Viscosity @ 104°F / 40°C | D445 | cSt | 110.3 | 180.3 | 212.2 | 243.7 |
| Kinematic Viscosity @ 212°F / 100°C | D445 | cSt | 15 | 20.2 | 24.2 | 24.0 |
| Viscosity Index | D2270 | - | 142 | 131 | 145 | 124 |
| SP. Gravity @ 15°C/ 60°F | D4052 | g/cm ³ | 0.880 | 0.889 | 0.888 | 0.890 |
| Flash Point (min) | D92 | °C | 223 | 236 | 232 | 234 |
| Pour Point (max) | D97 | °C | -33 | -24 | -24 | -21 |
| TBN | D2896 | Mg KOH/g | 8 | 8 | 8 | 8 |
| CCS, (°C) | D5293 | m.Pa.S | 6600 (-35°C) | 9500 (-15°C) | 9500 (-15°C) | 10,000 (-10°C) |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.