



SNOWMOBILE 2T

2-STROKE ENGINE LUBRICANT FOR SNOWMOBILE

PRODUCT DESCRIPTION:

Snowmobile 2T is an advanced fully synthetic oil specially formulated for 2-stroke engines in snowmobiles. It is formulated with selected esters for effective detergency and dispersancy characteristics. Synthetic base fluids give excellent low-temperature fluidity while maintaining excellent lubricating properties at high operating temperatures. Snowmobile 2T protects and performs under all operating conditions.

APPLICATION:

Snowmobile 2T is intended for 2-stroke engines with injector systems or lubricated by premix. It is suitable for both racing use and normal driving where very high performance is required. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Low ash formulation prevents deposits on pistons and ports.
- Mixes instantaneously with gasoline and remains stable.
- Excellent cold flow and lubricating properties at extreme temperatures.
- Reduces friction and wear to increase engine life

PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- ISO L-EGD
- JASO FD

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SNOWMOBILE 2T
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	7.5
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	41.4
Viscosity Index	ASTM D2270	-	150
TBN	ASTM D2896	Mg KOH/g	2
FLASH POINT	ASTM D92	°C	152
POUR POINT	ASTM D97	°C	-45
SPECIFIC GRAVITY	ASTM D4052	g/cm ³	TBR

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.