



TORQUE HD 10W

PRODUCT DESCRIPTION:

Torque HD 10W, an exceptional high-performance hydraulic oil blended from cutting-edge base oils and a precisely balanced additive system, catering to the diverse demands of heavy-duty hydraulic equipment. This product harnesses the power of ashless dispersants and metallic detergents in tandem with inhibitors, effectively controlling oxidation, wear, corrosion, and rust. Its versatility shines through as Torque HD 10W proves equally efficient in a broad spectrum of both on and off-highway hydraulic applications.

APPLICATION:

Torque HD 10W is specially designed to complement hydraulic systems and components that accompany equipment from top American, European, and Japanese manufacturers. This hydraulic oil excels in applications involving a wide range of ambient temperatures, making it a reliable choice for diverse environments. Its formulation includes excellent anti-wear properties, making it particularly suitable for hydraulic systems containing gears and bearings. The adaptability of Torque HD 10W extends to various industries, both on and off-highway, including trucking, construction, mining, quarrying, and agriculture. Its exceptional performance ensures optimal functionality and reliability across these demanding sectors.

FEATURES & BENEFITS:

- Good protection against oil thickening, high-temperature deposits, varnish, and oil degradation.
- Good anti-wear.
- Wide temperature range performance.
- Protects against rust and corrosion.

PERFORMANCE LEVELS: Meets or Exceeds:

- API CD
- API SF
- Eaton 35VQ25

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	TORQUE HD 10W
Kinematic Viscosity @100°C	ASTM D7042	cSt	6.11
Kinematic Viscosity @ 40°C	ASTM D7042	cSt	38.80
Viscosity Index	ASTM D2270	-	101
SP.Gravity @15°C	ASTM D4052	g/cm3	0.88
Total Base Number	ASTM D2896	mg KOH/g	7
Pour Point	ASTM D97	°C	-33
Flash Point	ASTM D92	°C	216

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.