



## AQUAPLUS GL-5 SAE 90

### PRODUCT DESCRIPTION:

AquaPlus GL-5 SAE 90 is a high-performance marine gear oil formulated with a special additive package to ensure wear protection, even in the presence of water contamination. It maintains stability under extreme pressure, high stress, and at elevated speeds.

### APPLICATION:

AquaPlus GL-5 SAE 90 marine gear oil provides outstanding corrosion protection and oxidation resistance.

### FEATURES & BENEFITS:

- Outstanding corrosion protection.
- High lubricating properties for friction reduction.
- Anti-corrosion protection.
- Excellent viscosity/temperature properties.

### PERFORMANCE LEVELS: Meets or Exceeds:

- API GL5

### TYPICAL PROPERTIES:

PARAMETERS	ASIM	UNIT	AQUAPLUS
SAE Grade			90
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	178.1
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	16.35
Viscosity Index	D-2270	-	96
Density@15°C/ 60°F	D-4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	D-92	°C	238
Pour Point (max)	D-97	°C	-12
Brookfield Viscosity @-40	D-2983	mPas	<150,000

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.